

Premium water based and biodegradable Tectyl cleaner and remover

Tectyl Biocleaner is a water based, biodegradable cleaner intended for removal of synthetic, animal, vegetable and mineral oils, greases and coatings. Tectyl Biocleaner can be used as to remove Tectyl corrosion preventative coatings. Tectyl Biocleaner leaves a clean and smooth surface.

Applications

Surface Preparation

The maximum performance of Tectyl Biocleaner can be achieved only when the metal surfaces to be protected are clean, dry and free of rust, oil and mill scale. CorPro recommends a substrate temperature of 10-35 °C at the time of product application.

Application

Tectyl Biocleaner is intended to be diluted in water (25%) for removing wax and oil based Tectyl layers up to the use of pure product (100%) with other layers or contaminated areas. For dilution demineralized or normal tap water can be used. The dilution and the exposure time depend on the nature and degree of pollution, the processing temperature and the chosen application method. Apply Tectyl Biocleaner, let it soak for several minutes and then rinse thoroughly with clean water. When necessary, repeat the treatment and/or increase the dosage. The use of hot water and mechanical support (such as pressurized water) will increase efficiency. When applying for the first time it is advised to test the product prior to use to prevent non intended paint removal. Applicable concentration depends on the application method and application area.

Features & Benefits

Excellent performance

Tectyl Biocleaner gives an excellent clean surface.

Safe to use

Tectyl Biocleaner is biodegradable.

Economical

The highly concentrated Tectyl Biocleaner is economical in use.

Widely applicable

Tectyl Biocleaner can be used in high pressure cleaning, tank-cleaning and floor scrubbers.

Trusted since 1930

Since 1930, Tectyl™ protective coatings have been extending the operational life of cars, trucks, buses and other vehicles and equipment. The Tectyl name is synonymous with quality coatings that are easy to apply, long-lasting and easy to remove when no longer required.

For more information on Tectyl products, programs and services please visit www.tectyleurope.com.

Health & Safety

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet.

Protect the environment

Comply with local regulations. Do not discharge into drains, soil or water.

Typical Properties

Typical property characteristics are based on current production. Whilst future production will conform to Tectyl specifications, variations in these characteristics may occur.

| Tectyl™ Biocleaner | |
|------------------------------|--------------|
| Density @ 20°C | 1.019 kg/ltr |
| Storage Temperature | 10 - 35°C |
| pH @ 20°C | 10 |
| Protection Indoor Months Na | PASS |
| Protection Outdoor Months Na | PASS |



<https://tectyleurope.com>

Storage

Tectyl Biocleaner should be stored at temperatures between 10-35 °C. Do not freeze Tectyl Biocleaner. Due to its composition Tectyl Biocleaner can be subject to postproduction viscosity changes during storage. Under proper storage conditions Tectyl Biocleaner is best before 24 months after production date.

Caution

Refer to The Safety Data Sheet for additional handling and first aid information.

State of the information

April 27, 2026

Validity

This information only applies to products manufactured in the following regions: Europe